
SHOW Documentation

Release 0.7.3

Joseph Durel

Dec 07, 2017

Contents:

1	Tutorial	1
1.1	Including & Compiling	1
1.2	Creating a Server	1
1.3	Handling a Connection	2
1.4	Reading Requests	2
1.5	Sending Responses	3
2	Classes & Types	5
2.1	Classes	5
2.2	Types	9
2.3	Throwables	10
3	Functions	13
4	Constants	15
5	Indices and tables	17

This shows the basic usage of SHOW; see the [examples](#) for a more thorough introduction.

1.1 Including & Compiling

For GCC and Clang, you can either link *show.hpp* to one of your standard include search paths, or use the `-I` flag to tell the compiler where to find the header:

```
clang++ -I "SHOW/src/" ...
```

SHOW is entirely contained in a single header file, you have to do then is include SHOW using `#include <show.hpp>`. With either compiler you'll also need to specify C++11 support with `-std=c++11`.

If you use [CMake](#) and don't have SHOW linked to said include path, you'll need to include the following in your *CMakeLists.txt*:

```
include_directories( "SHOW/src/" )
```

replacing "SHOW/src/" with wherever you've cloned or installed SHOW. Switch to C++11 mode with:

```
set( CMAKE_CXX_STANDARD 11 )  
set( CMAKE_CXX_STANDARD_REQUIRED ON )
```

1.2 Creating a Server

To start serving requests, first create a *server* object:

```
show::server my_server(  
    "0.0.0.0", // IP address on which to serve  
    9090,      // Port on which to serve  
);
```

That's it, you've made a server that sits there forever until it gets a connection, then hangs. Not terribly useful, but that's easy to fix.

1.3 Handling a Connection

For each call of `my_server.serve()` a single `connection` object will be returned or a `connection_timeout` thrown. You may want to use something like this:

```
while( true )
{
    try
    {
        show::connection connection( my_server.serve() );
        // handle request(s) here
    }
    catch( show::connection_timeout& ct )
    {
        std::cout
            << "timed out waiting for a connection, looping..."
            << std::endl
        ;
        continue;
    }
}
```

The server listen timeout can be a positive number, 0, or -1. If it is -1, the server will continue listening until interrupted by a signal; if 0, `server::serve()` will throw a `connection_timeout` immediately unless connections are available.

The connection is now independent from the server. You can adjust the connection's timeout independently using `connection::timeout()`. You can also pass it off to a worker thread for processing so your server can continue accepting other connections; this is usually how you'd implement a real web application.

1.4 Reading Requests

`request` objects have a number of `const` fields containing the HTTP request's metadata; you can see descriptions of them all in the docs for the class.

Note that these fields do not include the request content, if any. This is because HTTP allows the request content to be streamed to the server. In other words, the server can interpret the headers then wait for the client to send data over a period of time. For this purpose, `request` inherits from `std::streambuf`, implementing the read/get functionality. You can use the raw `std::streambuf` methods to read the incoming data, or create a `std::istream` from the request object for `std::cin`-like behavior.

For example, if your server is expecting the client to *POST* a single integer, you can use:

```
show::request request( test_server.serve() );

std::istream request_content_stream( request );

int my_integer;
request_content_stream >> my_integer;
```

Please note that the above is not terribly safe; production code should include various checks to guard against buggy or malignant clients.

Also note that individual request operations may timeout, so the entire serve code should look like this:

```

while( true )
{
    try
    {
        show::connection connection( my_server.serve() );
        try
        {
            show::request request( connection );
            std::istream request_content_stream( request );
            int my_integer;
            request_content_stream >> my_integer;
            std::cout << "client sent " << my_integer << "\n";
        }
        catch( const show::connection_timeout& ct )
        {
            std::cout << "got a request, but client disconnected!" << std::endl;
        }
        catch( const show::connection_timeout& ct )
        {
            std::cout << "got a request, but client timed out!" << std::endl;
        }
    }
    catch( const show::connection_timeout& ct )
    {
        std::cout << "timed out waiting for a connection, looping..." << std::endl;
        continue;
    }
}

```

If this feels complicated, it is. Network programming like this reveals the worst parts of distributed programming, as there's a lot that can go wrong between the client and the server.

See also:

- `std::streambuf` on cppreference.com
- `std::istream` on cppreference.com
- `std::cin` on cppreference.com

1.5 Sending Responses

Sending responses is slightly more complex than reading basic requests, aside from the error handling which should wrap both.

Say you want to send a “Hello World” message for any incoming request. First, start with a string containing the response message:

```
std::string response_content = "Hello World";
```

Next, create a headers object to hold the content type and length headers (note that header values must be strings):

```

show::headers_t headers = {
    { "Content-Type", { "text/plain" } },
    { "Content-Length", {
        std::to_string( response_content.size() )
    } }
};

```

Since it's a `std::map`, you can also add headers to a `headers_t` like this:

```
headers[ "Content-Type" ].push_back( "text/plain" );
```

Then, set the **HTTP status code** for the response to the generic *200 OK*:

```
show::response_code code = {  
    200,  
    "OK"  
};
```

Creating a response object requires the headers and response code to have been decided already, as they are marshalled (serialized) and buffered for sending as soon as the object is created. A response object also needs to know which request it is in response to. While there's nothing preventing you from creating multiple responses to a single request this way, most of the time that will break your application.

Create a response like this:

```
show::response response(  
    request,  
    show::http_protocol::HTTP_1_0,  
    code,  
    headers  
);
```

Finally, send the response content. Here, a `std::ostream` is used, as `response` inherits from and implements the write/put functionality of `std::streambuf`:

```
std::ostream response_stream( &response );  
response_stream << response_content;
```

See also:

- `std::map` on cppreference.com
- `std::ostream` on cppreference.com
- `std::streambuf` on cppreference.com

2.1 Classes

The public interfaces to the main SHOW classes are documented on the following pages:

2.1.1 Server

class `server`

The server class serves as the basis for writing an HTTP application with SHOW. Creating a server object allows the application to handle HTTP requests on a single IP/port combination.

`server (const std::string &address, unsigned int port, int timeout = -1)`

Constructs a new server to serve on the given IP address and port. The IP address will typically be `localhost/0.0.0.0/::`. The port should be some random higher-level port chosen for the application.

The timeout is the maximum number of seconds `serve()` will wait for an incoming connection before throwing `connection_timeout`. A value of 0 means that `serve()` will return immediately if there are no connections waiting to be served; -1 means `serve()` will wait forever (until the program is interrupted).

`~server ()`

Destructor for a server; any existing connections made from this server will continue to function

`connection serve ()`

Either returns the next connection waiting to be served or throws `connection_timeout`.

`const std::string &address () const`

Get the address this server is servering on

`unsigned int port () const`

Get the port this server is servering on

`int timeout () const`

Get the current timeout of this server

`int timeout (int)`

Set the timeout of this server to a number of seconds, 0, or -1

2.1.2 Connection

class connection

Objects of this type represent a connection between a single client and a server. A connection object can be used to generate *request* objects; one in the case of HTTP/1.0 or multiple in the case of HTTP/1.1.

The connection class has no public constructor (besides the move constructor), and can only be created by calling `server::serve()`.

connection (connection&&)

Explicit *move constructor* as one can't be generated for this class

~connection ()

Destructor for a connection, which closes it; any requests or responses created on this connection can no longer be read from or written to

const std::string &client_address

The IP address of the connected client

const unsigned int &client_port

The port of the connected client

int timeout ()

Get the current timeout of this connection, initially inherited from the server the connection is created from

int timeout (int)

Set the timeout of this connection independently of the server; the argument is a number of seconds, 0, or -1

See also:

- `server::timeout()`

2.1.3 Request

class request : public std::streambuf

Represents a single request sent by a client. Inherits from `std::streambuf`, so it can be used as-is or with a `std::istream`.

See also:

- `std::streambuf` on cppreference.com
- `std::istream` on cppreference.com

enum content_length_flag_type

A utility type for `unknown_content_length()` with the values:

Value	Evaluates to
NO	false
YES	true
MAYBE	true

const std::string &client_address

The IP address of the client that sent the request

const unsigned int &**client_port**

The port of the client that sent the request

bool **eof** () **const**

Returns whether or not the request, acting as a `std::streambuf`, has reached the end of the request contents. Always returns `false` if the content length is unknown.

See also:

- [`unknown_content_length`](#)

request ([`connection&`](#))

Constructs a new request on a connection. Blocks until a connection is sent, the connection timeout is reached, or the client disconnects. May also throw [`request_parse_error`](#) if the data sent by the client cannot be understood as an HTTP request.

See also:

- [`connection_timeout`](#)
- [`client_disconnected`](#)

request ([`request&&`](#))

Explicit [move constructor](#) as one can't be generated for this class

const [`http_protocol`](#) &**protocol**

The HTTP protocol used by the request. If `NONE`, it's usually safe to assume HTTP/1.0. If `UNKNOWN`, typically either a *400 Bad Request* should be returned, just assume HTTP/1.0 to be permissive, or try to interpret something from [`protocol_string`](#).

const std::string &**protocol_string**

The raw protocol string sent in the request, useful if [`protocol`](#) is `UNKNOWN`

const std::string &**method**

The request method as a capitalized ASCII string. While the HTTP protocol technically does not restrict the available methods, typically this will be one of the following:

GET	Common methods
POST	
PUT	
DELETE	
OPTIONS	Useful for APIs
PATCH	Relatively uncommon methods
TRACE	
HEAD	
CONNECT	

See also:

- [List of common HTTP methods on Wikipedia](#) for descriptions of the methods

const std::vector<std::string> &**path**

The request path separated into its elements, each of which has been URL- or percent-decoded. For example:

```
/foo/bar/hello+world/%E3%81%93%E3%82%93%E3%81%AB%E3%81%A1%E3%81%AF
```

becomes:

```
{
    "foo",
    "bar"
    "hello world",
    ""
}
```

const *query_args_t* &query_args

The request query arguments. SHOW is very permissive in how it parses query arguments:

Query string	Interpreted as
?foo=1&bar=2	{ { "foo", { "1" } }, { "bar", { "2" } } }
?foo=bar=baz	{ { "foo", { "baz" } }, { "bar", { "baz" } } }
?foo=&bar=baz	{ { "foo", { "" } }, { "bar", { "baz" } } }
?foo&bar=1&bar=2	{ { "foo", { "" } }, { "bar", { "1", "2" } } }

const *headers_t* &headers

The request headers

See also:

- [List of common HTTP headers on Wikipedia](#)

const *content_length_flag_type* &unknown_content_length

Whether the content length of the request could be interpreted

This member may be a bit confusing because it is “*un*-known” rather than “know”. It’s convenient for *content_length_flag_type* to evaluate to a boolean value, but there are two possible reasons the content length would be unknown. Either

1. the request did not send a *Content-Length* header, or
2. the value supplied is not an integer or multiple *Content-Length* headers were sent.

In many languages (including C++), 0 is `false` and any other value is `true`; so the boolean value needs to be `false` for a known content length and `true` for anything else.

unsigned long long content_length

The number of bytes in the request content; only holds a meaningful value if *unknown_content_length* is YES/`true`

2.1.4 Response

class response : public std::streambuf

Represents a single response to a request. Inherits from `std::streambuf`, so it can be used as-is or with a `std::ostream`.

SHOW does not prevent multiple response from being created or sent for a single request. Most of the time this is something that would break the application; however, under certain conditions in HTTP/1.1 multiple 100-type responses can be sent before a final 200+ response.

See also:

- `std::streambuf` on [cppreference.com](#)
- `std::ostream` on [cppreference.com](#)

response (*request*&, *http_protocol*, **const** *response_code*&, **const** *headers_t*&)

Constructs a new response in response to a request. The protocols, response code, and headers are immediately buffered and cannot be changed after the response is created, so they have to be passed to the constructor.

~response ()

Destructor for a response object; ensures the response is flushed

virtual void flush ()

Ensure the content currently written to the request is sent to the client

2.2 Types

enum http_protocol

Symbolizes the possibly HTTP protocols understood by SHOW. The enum members are:

HTTP_1_0	HTTP/1.0
HTTP_1_1	HTTP/1.1
NONE	The request did not specify a protocol version
UNKOWN	The protocol specified by the request wasn't recognized

There is no HTTP_2 as SHOW is not intended to handle HTTP/2 requests. These are much better handled by a reverse proxy such as [NGINX](#), which will convert them into HTTP/1.0 or HTTP/1.1 requests for SHOW.

class response_code

A simple utility `struct` that encapsulates the numerical code and description for an HTTP status code. An object of this type can easily be statically initialized like so:

```
show::response_code rc = { 404, "Not Found" };
```

See the [list of HTTP status codes](#) on Wikipedia for an easy reference for the standard code & description values.

The two fields are defined as:

unsigned short **code**

std::string **description**

class query_args_t

An alias for `std::map< std::string, std::vector< std::string > >`, and can be statically initialized like one:

```
show::query_args_t args = {
    { "tag", { "foo", "bar" } },
    { "page", { "3" } }
};
```

This creates a variable `args` which represents the query string `?tag=foo&tag=bar&page=3`.

See also:

- `std::map` on [cppreference.com](#)
- `std::vector` on [cppreference.com](#)

class headers_t

An alias for `std::map< std::string, std::vector< std::string > >`, `show::_less_ignore_case_ASCII`, where `show::_less_ignore_case_ASCII` is a case-insensitive [compare](#) for `std::map`.

While HTTP header names are typically given in `Dashed-Title-Case`, they are technically case-insensitive. Additionally, in general a given header name may appear more than once in a request or response. This type satisfies both these constraints.

Headers can be statically initialized:

```
show::headers_t headers = {
    { "Content-Type", { "text/plain" } },
    { "Set-Cookie", {
        "cookie1=foobar",
        "cookie2=SGVsbG8gV29ybGQh"
    } }
};
```

See also:

- `std::map` on cppreference.com
- `std::vector` on cppreference.com

2.3 Throwables

Not all of these strictly represent an error state when throw; some signal common situations that should be treated very much in the same way as exceptions. SHOW's throwables are broken into two categories — connection interruptions and exceptions.

2.3.1 Connection interruptions

class `connection_timeout`

An object of this type will be thrown in two general situations:

- A server object timed out waiting for a new connection
- A connection, request, or response timed out reading from or sending to a client

In the first situation, generally the application will simply loop and start waiting again. In the second case, the application may want to close the connection or continue waiting with either the same timeout or some kind of falloff. Either way the action will be application-specific.

class `client_disconnected`

This is thrown when SHOW detects that a client has broken connection with the server and no further communication can occur.

2.3.2 Exceptions

class `exception` : `std::exception`

A common base class for all of SHOW's exceptions

See also:

- `std::exception` on cppreference.com

class `socket_error` : *exception*

An unrecoverable, low-level error occurred inside SHOW. If thrown while handling a connection, the connection will no longer be valid but the server should be fine. If thrown while creating or working with a server, the server object itself is in an unrecoverable state and can no longer serve.

The nature of this error when thrown by a server typically implies trying again will not work. If the application is designed to serve on a single IP/port, you will most likely want to exit the program with an error.

class `request_parse_error` : *exception*

Thrown when creating a request object from a connection and SHOW encounters something it can't manage to interpret into a *request*.

As parsing the offending request almost certainly failed midway, garbage data will likely in the connection's buffer. Currently, the only safe way to handle this exception is to close the connection.

class `url_decode_error` : *exception*

Thrown by `url_decode()` when the input is not a valid *URL- or percent-encoded* string.

Note: `url_encode()` shouldn't throw an exception, as any string can be converted to percent-encoding.

class `base64_decode_error` : *exception*

Thrown by `base64_decode()` when the input is not valid *base-64*.

Note: `base64_encode()` shouldn't throw an exception, as any string can be converted to base-64.

`std::string url_encode (const std::string &o, bool use_plus_space = true)`

URL-encode a string `o`, escaping all reserved, special, or non-ASCII characters with [percent-encoding](#).

If `use_plus_space` is `true`, spaces will be replaced with `+` rather than `%20`.

`std::string url_decode (const std::string&)`

Decode a [URL-](#) or [percent-encoded](#) string. Throws [url_decode_error](#) if the input string is not validly encoded.

`string show : :base64_encode (const std::string &o, const char *chars = base64_chars_standard)`

[Base-64](#) a string `o` using the character set `chars`, which must point to a `char` array of length 64.

See also:

- [base64_chars_standard](#)
- [base64_chars_urlsafe](#)

`std::string base64_decode (const std::string &o, const char *chars = base64_chars_standard)`

Decode a [base-64](#) encoded string `o` using the character set `chars`, which must point to a `char` array of length 64. Throws a [base64_decode_error](#) if the input is not encoded against `chars` or has incorrect padding.

See also:

- [base64_chars_standard](#)
- [base64_chars_urlsafe](#)

CHAPTER 4

Constants

All constants are `const`-qualified.

class `version`

An anonymous `struct` containing information about the current SHOW version. Has the following members:

`std::string name`

The proper name of SHOW as it should appear referenced in headers, log messages, etc.

`int major`

The major SHOW version (X.0.0)

`int minor`

The minor SHOW version (0.X.0)

`int revision`

The SHOW version revision (0.0.X)

`std::string string`

A string representing the major, minor, and revision version numbers

`char *base64_chars_standard`

The standard set of [base-64 characters](#) for use with `base64_encode()` and `base64_decode()`

`char *base64_chars_urlsafe`

The URL-safe set of [base-64 characters](#) for use with `base64_encode()` and `base64_decode()`, making the following replacements:

- `+` → `-`
- `/` → `_`

CHAPTER 5

Indices and tables

- `genindex`
- `search`

S

show::base64_chars_standard (C++ member), 15
show::base64_chars_urlsafes (C++ member), 15
show::base64_decode (C++ function), 13
show::base64_decode_error (C++ class), 11
show::client_disconnected (C++ class), 10
show::connection (C++ class), 6
show::connection::~~connection (C++ function), 6
show::connection::client_address (C++ member), 6
show::connection::client_port (C++ member), 6
show::connection::connection (C++ function), 6
show::connection::timeout (C++ function), 6
show::connection_timeout (C++ class), 10
show::exception (C++ class), 10
show::headers_t (C++ class), 9
show::http_protocol (C++ enum), 9
show::query_args_t (C++ class), 9
show::request (C++ class), 6
show::request::client_address (C++ member), 6
show::request::client_port (C++ member), 6
show::request::content_length (C++ member), 8
show::request::content_length_flag_type (C++ enum), 6
show::request::eof (C++ function), 7
show::request::headers (C++ member), 8
show::request::method (C++ member), 7
show::request::path (C++ member), 7
show::request::protocol (C++ member), 7
show::request::protocol_string (C++ member), 7
show::request::query_args (C++ member), 8
show::request::request (C++ function), 7
show::request::unknown_content_length (C++ member),
8
show::request_parse_error (C++ class), 11
show::response (C++ class), 8
show::response::~~response (C++ function), 9
show::response::flush (C++ function), 9
show::response::response (C++ function), 8
show::response_code (C++ class), 9
show::response_code::code (C++ member), 9
show::response_code::description (C++ member), 9
show::server (C++ class), 5
show::server::~~server (C++ function), 5
show::server::address (C++ function), 5
show::server::port (C++ function), 5
show::server::serve (C++ function), 5
show::server::server (C++ function), 5
show::server::timeout (C++ function), 5
show::show::base64_encode (C++ function), 13
show::socket_error (C++ class), 10
show::url_decode (C++ function), 13
show::url_decode_error (C++ class), 11
show::url_encode (C++ function), 13
show::version (C++ class), 15
show::version::major (C++ member), 15
show::version::minor (C++ member), 15
show::version::name (C++ member), 15
show::version::revision (C++ member), 15
show::version::string (C++ member), 15